Delight Your Life

Featuring a refined navy-patterned mesh front panel, the DLITE FLEX mid-tower chassis combines comfort with sophistication and elevates your system's internal structure. Offered in sophisticated neutral tones and star-lined variants, its unified shapes and clean lines create a harmonious aesthetic, delivering a calming, contemporary presence to your home or office.

Next-Gen Ready

This streamlined ATX chassis supports up to 8 PCIe slots, ensuring seamless integration of the latest components and peripherals, including the latest graphics cards. Its adaptable layout is crafted to showcase high-end hardware while maintaining a balance of visual refinement and structural strength.



Versatile GPU Support

The chassis works seamlessly with NVIDIA's liser cable bracket, giving you the freedom to showcase your graphics card horizontally or vertically for a personalized display.

*Riser cable and GPU are not included in the package and need to be purchased separately.

Back-Connector Builds

Designed for a cleaner, more streamlined setup, this mid-tower supports back-connect MB. It hides cables behind the motherboard, enabling cable management and improved system organization.

* Compatible with ASUS, GIGABYTE and MSI Back-Connector motherboards.

Flexible Cooling

Offering support for up to 12 fans and 360 mm radiators, the DLITE FLEX is built for high-efficiency cooling for demanding systems. Whether air or liquid-cooled, DLITE FLEX is engineered to maintain optimal stability and temperatures low.

* Pre-Installed ARGB Fans (3 - Front, 1 - Rear

Model	AM120
Colors	Black
Fan Size	120 x 120 x 25 mm
Materials	ABS + PC
Rated Voltage	DC 12V
Rated Power	5.04W
Rated Current	0.4A
ARGB Rated Voltage	DC 5V
ARGB Rated Power	0.6W
ARGB Rated Current	0.12A
Speed Mode	PWM 810 - 1500 RPM
Air Flow	63.80 CFM
Air Pressure	1.29 mm H2O
LED	Addressable RGB
Connector to MB	4-Pin (1x), PWM, 3-Pin (5V, ARGB)
Noise Level	30.7 dB(A)
Bearing Type	Hydro-xc Bearing

* Inwin's products comply with RoHS regulations.
* Specifications may vary based on different regions.

Builder-Friendly Features

Specifications

Model	DLITE FLEX	
Model Number	IW-S36/IW-S36BO-WMO	IW-S36/IW-S36UPA-WMO
Colors	Mocha Blonde	Lilac Silver
Case Type	Mid Tower	
Materials	SPCC, Mirror Tempered+ ABS	
MB Compatibility	ATX, Micro-ATX, Mini-ITX	
Expansion Slots	8 + 2	
Maximum Compatibility	GPU: Up to 380 mm CPU: Heatsink Height: 165 mm	
I/O Ports	1 x USB 5.0 Gen 2x2 Type-C 2 x USB 5.0 Gen 3.2 HD Audio (CTIA - OMTP/MIC) Power Button with Green Switch Power Button	
Internal Drive Bays	2 x 3.5" & 2 x 2.5"	
Power Supply Compatibility	Air Cooling Fans: Front: 3 x 120 mm ARGB (Pre-installed) Top: 3 x 120 / 2 x 140 mm Rear: 1 x 120 mm ARGB (Pre-installed) Bottom: 2 x 120 mm (Screws required, 25mm) space required) Water Cooling Radiator: Front: 360 / 280 mm Top: 360 / 280 mm Rear: 120 mm	
	PSU - ATX12V Length up to 200 mm	
Product Dimensions (L x W x H)	464 x 345 x 508 mm 17.6 x 13.6 x 20.0"	
Package Dimensions (L x W x H)	586 x 322 x 582 mm 23.4 x 12.7 x 23.1"	
Net Weight	8.9 kg / 19.6 lb	
Gross Weight	10.4 kg / 22.9 lb	

* Inwin's products comply with RoHS regulations.
* Specifications may vary based on different regions.